Warning: Refer to current foreign charts and flight information publications for information within foreign airspace

L-22 Area Chart 1 of 2

L-21 PANELS ABCD 1°=223 NM

UNITED STATES GOVERNMENT FLIGHT INFORMATION PUBLICATION

IFR ENROUTE LOW ALTITUDE - U.S.

For use up to but not including 18,000' MSL

EFFECTIVE 0901Z 23 SEP 2010

TO 0901Z 18 NOV 2010

Consult NOTAMs for latest information

Published by the
U.S. Department of Transportation
Federal Aviation Administration
Aeronautical Services
http://AERONAVfaa.GOV

CORRECTIONS, COMMENTS, AND/OR PROCUREMENT

FOR RECOMMENDATIONS REGARDING FORMAT AND CONTENT CONTACT:
FAA, Aeronautical Information Services, AJV-321
1305 East-West Highway
Washington, D.C. 20591
Online at: http://1.usa.gov
E-mail: 9-AMC-Aeronav@faa.gov
Telephone: 1-866-295-8326

FOR CHARTING ERRORS CONTACT:
FAA, National Aeronautical Navigation Services, AJV-W1
SSMC-4, Stn. # 4339
1305 East-West Highway
Silver Spring, MD 20910-3281
Telephone 1-800-626-2677
Email: 9-AMC-Aeronav@faa.gov

Frequently asked questions (FAQ) are answered on our web site or http://1.usa.gov/1AERONAVFAA.GOV.
See the FAQs prior to contact via toll free number or email.

FOR PROCUREMENT CONTACT:
FAA, National Aeronautical Navigation Services
Distribution Team, AJV-W
6500 South MacArthur Blvd.
Oklahoma City, OK 73169
Online at: http://AERONAV.FAA.GOV
E-mail: 9-AMC-Aeronav@faa.gov
Tel: 1-800-638-8972 - Fax: 301-436-6829
or any authorized chart agent

MILITARY
For Corrections Information, See Chapter 11 of General Publication for Aeronautical Charts and Publications, Aeronautical Chart and Flight Information Publications.

L-21 is intended for offshore navigation only.
Detailed onshore information has been intentionally omitted.
Refer to charts L19/20, L-22, L-23/24 for detailed onshore information.

ATTENTION

THIS CHART CONTAINS OFF ROUTE OBSTRUCTION CLEARANCE ALTITUDES (OROCA).
The off route obstruction clearance altitudes shown in quadrangles bounded by tinted lines of latitude and longitude provide at least 1000 feet of clearance (2000 feet in designated mountainous areas). This altitude is based on information available concerning the highest terrain features in each quadrangle, including terrain and obstructions. OROCA provides obstruction clearance with a 1000 foot buffer in designated non-mountainous areas and a 2000 foot buffer in designated mountainous areas within the United States. For areas in Mexico and the Caribbean which are bounded outside of the U.S. MSE, OROCA provides obstruction clearance with a 2000 foot buffer. This altitude is provided for obstruction clearance only. It may not provide adequate navigation signal or communication coverage, and would not be consistent with altitudes assigned by Air Traffic Control.

Example: 12,500 feet 12 5

23 SEP 2010
UNITED STATES

L-21

Federal Aviation Administration